

FL960 Wheel Loader Specifications

LOVOL

FL960





ZF 4BP 210 Countershaft, Auto shift

Transmission System
Transmission type

Item	
Operating Weight	19000kg
Static Tipping Load (straight)	13770kg
Static Tipping Load (at full turn)	11000kg
Rated Load	5500kg
Max. Traction Force	160kN
Max. Gradeability	29°
Max. Dump Clearance	3100mm
Dump Reach	1130mm
Wheel Tread	2150mm
Wheelbase	3350mm
Overall Dimension (L×W×H)	8650mm×2980mm×3460mm

Torque Converter	single-stage, three elements
Gear Shift	4 forward, 3 reverse
Driving Axles	
Axles Type	MERITOR Wet axle
Differential front type	Limited slip
Differential rear type	Limited slip
Steering System	
Steering System	Load-sensing hydraulic articulated steering.
Steering configuration	Articulated
Steering Angle Each Direction	37°
Min. Turning Radius	7140mm
Tyre	
Tyre Size	23.5-25 20PR
Hydraulic System	
Closed center type hydraulic system with LS type variable displacement piston type pumps.	
Hydraulically driven cooling fan	
Electro hydraulic control lever	
Rate Control(option)	
Brake System	
Service Brake	Full Hydraulic Brake

Electro-hydraulic Brake

Service Refill Capacity

Engine Model

Emission Standard

Max. Torque

Displacement

Number of Cylinders

Max.Engine Rated Power

Fuel Tank	350L
Hydraulic Tank	235L
Engine Oil	21L

LOVOL HEAVY INDUSTRY GROUP CO.,LTD.

Address: No. 75, Huanghe East Road, Huangdao District, Qingdao City, Shandong Province, China.

WEICHAI WP10HG230E670

1200N·m (1400-1600rpm)

StageV

6 in line

170kW/2200rpm

Website: en.wlovol.com E-mail: zhangkuisheng@lovol.com TEL: +86-17685707806 Facebook: Cons Lovol

Park Brake

As manufacturer, LOVOL has right to constantly upgrade and improve our products without informing to customers. The pictures in literatures are for reference only, the detailed specifications are subject to real products.



Engine Model WE
Rated Power 170
Operating Weight 190
Bucket Capacity 3.3
Max. Breakout Force 165

WEICHAI WP10H stage V 170kW/2200rpm 19000kg 3.3-5.0m³

